


Lighting Tower LED Upgrade Kit

200W High Output Disc - 140 Lm/W

A high output LED flood light kit, ideal replacement for 4 x 400W metal halide lighting towers

- Integrated ballast / driver
- 5000K cool white colour temperature
- Average life of 50,000 hours
- Tough non-corrosive aluminium die-cast housing
- Rated IP66 - ideal for outdoor use
- 5 year warranty
- Adjustable tilt and turn brackets
- 1 metre cable



KIT
200WUPGRADEKIT



200W Light Output
Over 3000m² area coverage
at 20 lux average

PRODUCT CODE	VOLTAGE	WATTAGE	LUMENS	BEAM ANGLE	WEIGHT
200WUPGRADEKIT	100-240V 50/60Hz	800W	112,000	90°	34Kg
200WHEAD	100-240V 50/60Hz	200W	28,000	90°	8.5Kg

TOTAL EQUIPMENT SOLUTIONS

SINGLE HEAD SPECIFICATIONS

ELECTRICAL SPECIFICATIONS	
LED Power:	200W
Operating Voltage:	100-240V AC
Operating Temperature:	-40°C ~ 50°C
Operating Humidity:	10% ~ 90%
Power Factor (PF):	>0.95
Power Supply Efficiency:	>90%
PHOTOMETRIC SPECIFICATIONS	
Initial Luminous Flux:	28,000lm
Colour Rendering Index (CRI):	Ra > 70 (>80 optional)
Colour Temperature:	5,000 - 6,500K
MECHANICAL SPECIFICATIONS	
IP & IK Rating	IP67 & IK10
Lifetime	50,000 hours - L70, @25°C
Heat Radiator	Anodised Aluminium
Lens	PC (Polycarbonate)
Fixture Dimension	ø400 x 447mm



The Philips LUXEON® T emitters are illumination grade LEDs designed to deliver high efficacy with high flux density to enable right beam control in directional and high lumen applications.



The highly efficient Mean Well LED driver offers longevity and a 5 year product warranty.

TOTAL EQUIPMENT SOLUTIONS



Ritelite (Systems) Ltd, Meadow Park, Bourne Road, Essendine, Stamford, Lincolnshire, PE9 4LT
Tel. 01780 758585 Fax. 01780 765700 E-mail. sales@ritelite.co.uk Web. www.ritelite.co.uk